



Radio

PROCESS SENSORS
CORPORATION

HHRF Handheld Radio Frequency Moisture Gauge

The Ultimate in Handheld Portable Design

Product Overview

Process Sensors' new **HHRF** handheld moisture sensor is a pure dielectric RF moisture gauge, using enhanced phase lock referencing on the generated frequency to measure shift in resonant frequency due solely to changes in moisture throughout the sampling volume. The measurement is not influenced by ionic strength.

The ultimate in portable design. With an easy to grip handle, the **HHRF** is light weight and simple to maneuver. **HHRF** features a choice of highly visible display modes – numerical or graphical, and also incorporates ten (10) user programmable calibrations for current and future needs. Measurement modes include: free run, time average, plus a pre-zero function and gauge standardisation.

Operation is simple, using a touch membrane with seven keys. The user selects the function required and pushes the up/down keys to edit calibration variables.

The **HHRF**'s robust IP65/NEMA4 enclosure and its extended battery life promote longevity and practicality with up to six hours of use between charges. A USB interface is provided for download of stored measurements.



Features

- **Extended operational life between recharges via:**
 - Auto power down
 - Efficient signal processing
 - Low energy use display
- **Minimal recharge time of 1 hour**
- **Light weight ergonomic design**
- **Enhanced Phase Lock Referencing**
- **10 User Programmable calibrations**
- **Pre Zero and Gauge Standardisation Functions**

Specifications: HHRF

Measured Constituents: _____ Moisture
Penetration Depth: _____ Dependant on application
Operating Temperature: _____ 10-40°C (50-100°F)
Calibrations: _____ 10
Power: _____ 9 VDC
Enclosure: _____ IP65/NEMA4
Unit Dimensions: _____ (LxWxH), 11 x 4 x 3 inches
(281x 105 x 85 mm)
Weight: _____ 5 lbs (1 kg)
Display: _____ Two Line LED



PROCESS SENSORS
CORPORATION



OneTemp^opty ltd
MEASURE | CONTROL | RECORD
www.onetemp.com.au
1300 768 887

For more information on Process Sensors instruments and accessories, visit our website at: www.processsensors.com

HEADQUARTERS

United States - Process Sensors Corporation
113 Cedar Street Milford, MA 01757 USA
Tel: (508) 473-9901 | Fax: (508) 473-0715
info@processsensors.com

Europe - Process Sensors Europe

Unit 4, Adelaide House Corbygate Business Park
Corby, Northants NN17 5JG United Kingdom
Tel: 01536 408066 | Fax: 01536 407813
info@processsensors.com
www.processsensors.co.uk

Eastern Europe - Process Sensors Polska

Biuro Informacyjne Techniki Pomiarowej
03-980 Warszawa ul. Znanieckiego 16/23 Poland
Tel: (48) 22 6739526 | Fax: (48) 22 6739527
tstachowiak@poczta.onet.pl