

IONIX INSTRUMENTS

DO10 / DO50 HANDHELD SERIES

Optical Dissolved Oxygen Meter

OneTemp^{pty Ltd}
MEASURE | CONTROL | RECORD
www.onetemp.com.au
1300 768 887



Comes in strong carry case

Advanced
Optical Sensor



Connections for probes



USB port for data transfer
and power supply



Advanced intelligent meter

Advanced fluorescence optical sensor

- No oxygen consumption, stable display in both static water and dynamic water.
- Simple to use, no need to warm-up and frequent calibration, fast response.
- Reliable structure, no electrode membrane or electrolyte, the service life of fluorescence cap > 8000 hours.
- Fluorescence cap has lightproof coating, anti-interference which is not affected by light and chemicals.
- Equipped with electrode calibration sheath which makes calibration and maintenance more convenient and reliable.

- Automatic temperature compensation and automatic pressure compensation.
- Large size LCD with white backlight, clear display.
- Reading stable display mode and automatic lock on display mode.
- DO50 model: automatic salinity compensation, real time clock, timing store, USB output.
- In accordance with IP57 waterproof rating, equipped with carrying case.



Tester



DO Probe



Sensor Cap



WATERPROOF



		 DO10		 DO50	
DO	Measuring range	0-200%; 0-20.0mg/L		0-200.0%; 0-20.00mg/L	
	Resolution	1%, 0.1mg/L (ppm)		0.1%, 0.01mg/L (ppm)	
	Accuracy	±0.1 mg/L (0~8mg/L) ±0.2 mg/L(8~20mg/L)		±0.1 mg/L (0~8mg/L) ±0.2 mg/L(8~20mg/L)	
	Calibration point	Zero oxygen & oxygen saturation		Zero oxygen & oxygen saturation	
	Temperature compensation	Automatic		Automatic	
	Pressure compensation	Automatic		Automatic	
	Salinity compensation	Manual		Automatic or manual	
Temp.	Measuring range	0 ~ 50.0°C		0 ~ 50.0°C	
	Resolution	0.1 °C		0.1 °C	
	Accuracy	±0.5°C		±0.5°C	
Reading stable indication		Yes		Yes	
Automatic lock on		Yes		Yes	
Display screen		Backlight LCD		Backlight LCD	
Data logging		No		500group(with time and date)	
Real time clock		No		Yes	
Signal output		No		USB	
IP rating		IP57		IP57	
Power		AA battery×3 battery life>200 hours		AA battery×3 battery life>200 hours	
Product set		DO10 meter DO electrode(3M) Calibration sheath + carrying case		DO50 meter DO electrode (3M) salinity electrode(3M) Calibration sheath combination probe cap USB cable + CD + carrying case	



IONIX INSTRUMENTS
www.ionixinstruments.com

OneTemp^{pty ltd}
MEASURE | CONTROL | RECORD
www.onetemp.com.au
1300 768 887

